

ILVA TECHNICAL DATA SHEET

PRODUCT SERIES: KLIMA

PRODUCT CODE: HTMB06x Series

DESCRIPTION: KLIMA UNICO Clear Self Sealer

PRODUCT PREPARATION:	HTMB06x Water	KLIMA Unico Clear Self Sealer Thinner	100 parts by weight or volume 0-5 % by weight or volume
-----------------------------	------------------	--	--

USES: Three coats. To be used as a self-sealer or final coat over tinted impregnator or colors. Not to be used as a clear finish over natural wood. For outdoor use. Excellent for finishing and protecting your exterior doors, railing, columns, decks, or exterior furniture. Easy application, excellent performance and environmentally safe.

APPLICATION SYSTEM: Spray, gravity gun, brush

FILM THICKNESS: 2.4-3.2 mils wet by brush, 3.2-4 mils wet by spray

GENERAL PROPERTIES:	Specific Gravity, gr/cc	1.020+/- .03
	Viscosity as supplied (Ford 6 cup)	20 +/- 2
	Solids, % by weight:	25 +/-2
	Thinner:	Water
	% of dilution:	5-6% depending upon equipment

DRYING TIME: (at 20°C/68°F)	Air Dry with ventilation, dry to handle:	
	Room temperature drying @18-22°C, 64-72°F	4 hours
	Stackable after room temperature drying	24 hours with spacers
	Hot air stages tunnel drying (20-40-60°C) (68-104-140°F)	
	complete drying	2 hours
	Stackable after jet hot air drying	8 hours with spacers

(Drying times can vary according to temperature, ventilation and relative humidity)

AVAILABLE SHEENS:	HTMB06B	80 Sheen
	HTMB06H	25 Sheen
	HTMB066	10 Sheen

ADDITIONAL TIPS: This product combines the stain, sealer and topcoat all in one product. All that is needed is to apply 3 coats of the same product. It can be used on table tops, furniture, doors, windows, and railings. The performance in sun and rain is exceptional.

SHELF LIFE: 12 Months

STORAGE: Store in a tightly closed container at room temperatures (18 -25 °C/64 -75 °F) and protect from moisture and foreign material. Do not store at temperatures below 7°C (45°F)

DATE OF ISSUE: 2-18, 4-19

**IC & S, P.O. BOX 10845, LANCASTER, PA 17605
(800) 220-4035**

EVERY REASONABLE PRECAUTION IS TAKEN IN THE MANUFACTURE OF OUR PRODUCTS TO INSURE THAT THEY COMPLY WITH OUR STANDARDS. INFORMATION GIVEN IS CORRECT TO THE BEST OF OUR KNOWLEDGE. ANY SUGGESTIONS MADE BY US COVERING THE USE OF OUR PRODUCTS ARE BASED ON EXPERIENCE AND/OR TESTS BELIEVED TO BE RELIABLE. HOWEVER, BECAUSE THE USE OF ANY PRODUCT OF OUR MANUFACTURE IS COMPLETELY BEYOND OUR CONTROL, INCLUDING FOR EXAMPLE, THE METHOD AND CONDITIONS OF APPLICATION, NO GUARANTEE OR WARRANTY, EXPRESSED OR IMPLIED, IS MADE. MANUFACTURER'S MAXIMUM LIABILITY SHALL BE TO REPLACE SUCH QUANTITY OF PRODUCT DETERMINED BY OUR LABORATORY TO BE DEFECTIVE. USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS INTENDED USE AND ASSUME ALL RISK AND LIABILITY IN CONNECTION THEREWITH.